



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: HT1210ISOCTR

### 2U rack/console component power center w/ digital IR remote for all audio/video components - Isobar Audio/Video Power Center

#### Highlights

- 12 AC outlets arranged in three filter banks; 10-ft. power cord
- 4 sequenced, individually controllable AC outlets; IR remote control device included
- 5700-joule surge suppression rating
- 3-line HD-compatible gold coaxial surge protection
- 1-line tel/modem surge protection with built-in splitter; 1-line Ethernet surge protection
- \$150,000 [Ultimate Lifetime Insurance](#) (USA/Canada only); lifetime product warranty



#### Description

Tripp Lite's HT1210ISOCTR Isobar Audio/Video Power Center provides ultimate protection 5700 joules stopping damaging surges and filtering disruptive EMI/RFI line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio; and longer component life spans. Perfect for large home/business theater installations, high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. Features 12 AC outlets arranged in 3 filter banks: Analog, Digital and High Frequency. Four AC outlets are sequenced and individually controllable; IR remote control device included. Dual digital LED displays plus 12 additional LEDs show incoming voltage, current connected equipment load and a variety of operating conditions. Three-line HD-compatible gold coaxial surge protection, 1-line tel/modem protection with built-in splitter (1 line in/2 lines out) and 1-line Ethernet protection safeguard audio/video components on all connections. Metal housing; 2U rackmount/console design with included hardware and removable console feet, 10-ft. power cord with right-angle plug. Includes 6-ft. gold coaxial cable, 6-ft. phone cable and 6-ft. network cable. \$150,000 [Ultimate Lifetime Insurance](#) coverage (USA/Canada only); lifetime product warranty.

#### Applications

- Large home/business theater installations, high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more

#### Package Includes

- HT1210ISOCTR Isobar Audio/Video Power Center
- One hand-held IR remote control device; one 6-ft. gold coaxial cable; one 6-ft. phone cable; one 6-ft network cable
- Color-coordinated outlet/plug labels
- Hardware for 2U rackmounting
- Instruction manual with warranty information

#### Features

- 5700-joule surge suppression rating with EMI/RFI line noise filtering helps components perform at their peak (sharper, crisper video; deeper, fuller audio; and longer component life spans)
- Exclusive Isolated Filter Banks eliminate interference between connected components
- 3 built-in filter banks: Analog, Digital, High Current
- Metal housing safely withstands the strongest surges

- 12 surge-protected NEMA 5-15R AC outlets safeguard all audio/video components
- 4 sequenced, individually IR-controllable AC outlets work with either included remote device or with user-supplied universal learning IR remote to facilitate orderly system startup and shutdown
- 3 sets of surge-protected, HD-compatible 2.2 GHz Type F gold coaxial connectors safeguard components on cable, satellite and antenna connections; one 6-ft. gold coaxial cable included
- 1-line tel/modem surge protection safeguards personal video recorders (PVRs) on a single dial-up connection. Built-in splitter (1 jack in/2 jacks out) allows simultaneous connection of two devices sharing a single line; one 6-ft. phone cable included
- 1-line Ethernet surge protection safeguards equipment on a 10/100 Base T network connection; one 6-ft network cable included
- 10-ft. power cord with right-angle NEMA 5-15P plug permits convenient placement anywhere within a home/business theater system
- 2 digital LED displays and 12 additional diagnostic LEDs alert user to input voltage levels, component load levels and 4 operational conditions (power, protection, grounding, selected outlets)
- 2U rackmount or console installation options; rackmount hardware and removable rubber console feet included
- Illuminated master switch provides one-touch power control over all components
- 15A circuit breaker protects against dangerous system overload
- Fail-safe thermal fusing acts like an additional circuit breaker, shutting down the unit and connected equipment in the event of a catastrophic surge
- Audible alarm immediately alerts user to damaged protection circuitry; perfect for installations where LEDs aren't normally viewed
- Color-coordinated outlet/plug labels match outlets to component power cords for easy identification
- TUV tested to UL standards 1449, 60950 and 962A
- \$150,000 [Ultimate Lifetime Insurance](#) covers connected components against surge damage for life! (USA/Canada only)
- Lifetime product warranty

## Specifications

OVERVIEW	
Intended Application	Audio/Video
SYSTEM OVERVIEW	
Voltage compatibility (VAC)	120
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output watts	1440
Output volt amp capacity (amps)	12
Overload protection	15A circuit breaker
Outlet quantity / type	12 NEMA 5-15R
INPUT	
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input plug features	Right-angle plug
Input cord length (ft.)	10
Input cord length (m)	3
Input cord gauge, type	14 gauge, SJT
LEDS ALARMS & SWITCHES	
Alarms	Audible alarm
Switches	Illuminated on/off power switch

<b>Diagnostic LEDs</b>	Dual digital LED displays and 12 additional diagnostic LEDs alert user to input voltage levels, component load levels and 4 operational conditions (power, protection, grounding, selected outlets)
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC suppression joule rating</b>	5700
<b>AC suppression response time</b>	NM = instantaneous CM = < 1 ns
<b>Protection modes</b>	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
<b>Safe thermal fusing</b>	Yes
<b>UL1499 let through rating</b>	330V - UL verified
<b>EMI / RFI filtering</b>	Yes
<b>Isolated filter banks</b>	3
<b>DATALINE SURGE SUPPRESSION</b>	
<b>Telephone/DSL Protection</b>	Yes
<b>Telephone/DSL Protection Details</b>	1 line
<b>Cable (Coax) Protection</b>	Yes
<b>Cable (Coax) Protection Details</b>	3 line (2.2 GHz Bandwidth)
<b>Network (Ethernet) Protection</b>	Yes
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	16
<b>Shipping weight (kg)</b>	7.3
<b>Unit Dimensions (HWD/in)</b>	3.5 x 17.5 x 12
<b>Unit Dimensions (HWD/cm)</b>	8.8 x 43.8 x 30.5
<b>Shipping Dimensions (HWD/in)</b>	7.5 x 21.5 x 15.0
<b>Shipping Dimensions (HWD/cm)</b>	19.1 x 54.6 x 38.1
<b>Unit weight (lbs)</b>	13.5
<b>Unit weight (kg)</b>	6.1
<b>Material of construction</b>	Metal
<b>Mounting accessories included</b>	2U rackmounting hardware
<b>Receptacle Color</b>	Black
<b>AC line cord color</b>	Black

<b>Style</b>	Rack/Console
<b>Form factors supported</b>	2U rackmount/console installation
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	Attractive black housing and receptacles with silver faceplate
<b>Right-Angle Plug</b>	Yes
<b>CERTIFICATIONS</b>	
<b>UL1449 3rd Edition (AC Suppression)</b>	UL1449
<b>UL1283 (EMI Filter)</b>	UL1283
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	RoHS, TUV tested to UL standards 1449 & 962A
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	Lifetime
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$150,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3500](http://www.tripplite.com/en/products/model.cfm?txtModelID=3500).

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.