



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUMH15ATNET

### Switched, Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching, individual outlet control and remote network interface

#### Highlights

- 1U switched PDU with digital current monitoring, network interface and 8 individually controllable outlets
- 15A 120V capacity with 8 NEMA 5-15R outlets and 5-15P input connections
- Built in SNMP network interface supports individual outlet control and remote monitoring of PDU loading and site electrical conditions
- Optional Auto Transfer Switch (ATS) supports a variety of advanced fault-tolerant and redundant networking applications
- Supports 2-7 ms. transfer between included primary and secondary line cords, even with out of phase power sources



#### Description

Tripp Lite's 120V 15A metered PDU system with Automatic Transfer Switching (ATS) is an 8 outlet PDU with a digital display to indicate total PDU power consumption in amps. Outlets are factory programmed for sequential turn-on at 250 millisecond intervals when the PDU is first energized to prevent inrush-related equipment interaction on startup. Installed web/network monitoring card enables remote power monitoring and control. Remotely displays status of input power, load capacity, and outlet power condition via secure network or web browser interface. Offers individual outlet control to power on, off, or cycle AC output to regain control of locked-up servers and other network devices. Load ramping and shedding provides programmable power management to any type of network configuration. Supports notification and logging of input power status, event notification, output power and PDU loading conditions. Supports 1U rackmount installation in a 2 or 4 post racks. Included are 8 NEMA 5-15R outlets and two 12 ft. 5-15P optional-use dual cords for auto-transfer switching (ATS) option.

Optional integrated ATS / Auto-Transfer Switch provides a redundant power option for networking and server applications with non-redundant internal power supplies. In ATS mode, the attached power cord serves as the PRIMARY input and the included detachable cable serves as the SECONDARY input to the ATS. The ATS will normally maintain continuous output to all outlets as derived from the primary input cable. If the primary power source becomes unstable or fails altogether in relation to the secondary, the ATS will switch over to the secondary power source until the primary input is restored and stable. Super-fast switchover between primary and secondary power sources occurs within 2-7 milliseconds. ATS functionality is supported by any two 120V AC power sources, regardless of phase angle, to offer support for a variety of advanced redundant power networking applications. Enables fault tolerant hot-swappable UPS protection when used with a single UPS and fully redundant UPS protection when each cord is connected to a separate UPS system. In a two-UPS environment, the primary input cable must be supported by a full time sine wave online UPS. Tripp Lite SmartOnline series is highly recommended for use as the primary UPS in a two-UPS application. ATS configurations utilizing separate mains circuits, backup generators and even separate utility power grid feeds are fully supported. On-board ATS processor constantly evaluates power quality on both input sources to prevent transfer to the secondary source when unavailable or of lower quality than the primary source. Front input LED's display primary or secondary power availability.

#### Applications

- Ideal for configurations requiring a networked managed PDU to remotely reboot individually locked-up devices such as network switches, hubs, servers, etc.
- Optional-use ATS function makes this system ideal for adding redundancy to single corded devices

- ATS function adds hot-swap and maintenance bypass function to standard UPS configurations

#### Package Includes

- PDU with attached 5-15P input power cord
- Detachable C13 to NEMA 5-15P 12 ft/3.6m power cord for optional secondary input
- Installable 1U mounting brackets
- User manuals with warranty information

## Features

- 120V 15A metered PDU system with Automatic Transfer Switch (ATS)
- Dual input cords, one attached (primary) and one optional-use detachable cord (secondary)
- Included cordsets support 5-15P plug-in connection
- Front panel digital ammeter displays power consumption in amps.
- Web/Network monitoring card enables remote power monitoring and control of power to each outlet
- 8 built-in NEMA 5-15R output receptacles
- Optional ATS function enables setup for hot-swappable UPS maintenance bypass, dual UPS protection or dual AC input redundancy for critical single-corded network hardware (ATS function requires the use of a full time sine wave UPS, like Tripp Lite's SmartOnline series)
- ATS functionality is supported by any two 120V AC power sources, regardless of phase angle, to offer support for a variety of unique redundant power applications
- Small 1U rackmount format installs in only one rack space with a maximum installed depth of 14.5 inches
- Also supports 0U vertical mounting in the cable management area of many rack enclosures
- Individually controlled outlets provide load management to networked equipment
- Sequential outlet turn on eliminates power up in-rush of connected devices on initial power up
- Super-fast switchover between primary and secondary power sources occurs within 2-7 milliseconds

## Specifications

OVERVIEW	
Model Type	Switched; ATS/Auto Transfer Switches
SYSTEM OVERVIEW	
Voltage compatibility (VAC)	120
OUTPUT	
Frequency compatibility	60 Hz
Output VA	1800
Output nominal voltage	120V
Outlet quantity / type	8 NEMA 5-15R
Customized load management receptacles	8 individually controlled outlets
INPUT	
Recommended Electrical Service	120V
Maximum Input Amps (A)	15
Input connection type	2 NEMA 5-15P
Plug Type	NEMA 5-15P (15A 120V)
Input cord length (ft.)	12
LEDS ALARMS & SWITCHES	

<b>Front panel LEDs</b>	10 front panel LEDs display power on - off status for each outlet, plus 2 LEDs for power status on each input line cord. Digital Current Meter display shows total output power consumption in amps.
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	15.2
<b>Shipping weight (kg)</b>	6.9
<b>Unit Dimensions (HWD/in)</b>	1.75 (1U) x 17.5 x 14.5
<b>Unit Dimensions (HWD/cm)</b>	4.44 x 44.4 x 36.8
<b>Shipping Dimensions (HWD/in)</b>	6.25 x 22.5 x 23.5
<b>Shipping Dimensions (HWD/cm)</b>	15.9 x 57.2 x 59.7
<b>Unit weight (lbs)</b>	11
<b>Unit weight (kg)</b>	5
<b>Material of construction</b>	Steel
<b>Style</b>	Rackmount
<b>Form factors supported</b>	1U rackmount
<b>ENVIRONMENTAL</b>	
<b>Relative Humidity</b>	Up to 95% (non-condensing)
<b>COMMUNICATIONS</b>	
<b>SNMP compatibility</b>	Yes, pre-installed <a href="#">SNMPWEBCARD</a> provides remote monitoring via web, telnet, and SNMP management systems. Remote management gives user ability to turn connected loads on or off individually
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	Black 1U rackmount steel chassis
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL 60950-1 (USA, Canada), Class A (Emissions), NOM (Mexico), RoHS compliant
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2 years

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
SNMP Accessories	<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	-
Extended Warranties	<a href="#">WEXT3-PDU-ATNET</a>	3-Year Extended Warranty - For Switched PDUs ending with ATNET	-
Extended Warranties	<a href="#">WEXT5-PDU-ATNET</a>	5-Year Extended Warranty - For Switched PDUs ending with ATNET	-
Rack Accessories	<a href="#">SR SWITCH</a>	Magnetic Door Switch Kit (2-pack for front and rear doors; requires ENVIROSENSE.)	-

Rack Accessories	<a href="#">SRCABLEDUCT1U</a>	1U Horizontal Cable Manager (Finger duct with cover.)	-
Rack Accessories	<a href="#">SRCABLERING1U</a>	1U Horizontal Cable Manager (Flexible ring type.)	-
Rack Accessories	<a href="#">SRCABLERING2U</a>	2U Horizontal Cable Manager (Flexible ring type.)	-
Power Cables	<a href="#">P005-002</a>	2-ft. Heavy-Duty 14AWG Power cord ( IEC-320-C13 to IEC-320-C14)	-
Power Cables	<a href="#">P005-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	-
Power Cables	<a href="#">P005-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	-
Power Cables	<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	-
Power Cables	<a href="#">P012-006</a>	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	-
Power Cables	<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	-
Power Cables	<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	-
Power Cables	<a href="#">P032-007</a>	7-ft. 12AWG Heavy Duty Power cord ( IEC-320- C13 to IEC-320-C20)	-
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord ( IEC-320-C19 to NEMA 5-15P)	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3495](http://www.tripplite.com/en/products/model.cfm?txtModelID=3495).

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.