Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PDUNV

Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment

Highlights

- Versatile PDU system supports 1U rackmount, 0U vertical mount, wall mount and under-counter installation
- Supports 100-250V power distribution via 12 C13 and 2 C19 outlets
- 10 foot / 3m attached power cord with C20 power input connection
- Included pack of 5 secured C19 adapters support plug-in connection via C14, L6-20P, L5-20P, 5-20P or 5-15P input plug
- 16A circuit breaker

Description

The PDUNV Universal Rackmount PDU offers multi-outlet power distribution for worldwide low and high voltage applications from 100-250V via built-in C19 and C13 outlets. 1U rackmount chassis also supports 0U vertical mount, wall mount and under-counter mount installation in a variety of applications. Attached 10 foot, 3m input cord offers a C20 plug-in connection. Pack of 5 included C19 adapters with secure locking retainer clip enables plug conversion to C14, L6-20P, L5-20P, 5-20P and 5-15P. 16A circuit breaker, grounding lug. Mounting hardware included.

Applications

- Multi-outlet power distribution unit is the ideal means of powering multiple loads in 19 inch rackmount, wallmount and under-counter applications. Ideal for distribution of UPS, generator or commercially derived AC power to multiple equipment loads.

Package Includes

- 1U rackmount PDU
- Mounting hardware
- Set of 5 plug adapters
- User manual with warranty information

Features

- PDUNV supports multi-outlet power distribution with worldwide compatiblity for 100-250V applications
- Supports standard 1U rackmount installation, with additional support for 0U vertical mount, wallmount and under-counter mount installation
- Includes 2 C19 high current and 12 C13 low current outlets
- Includes 10 foot, 3m attached input power cable with C20 input plug-in connection (connects to C19 100-250V)
- Pack of 5 included C19 adapters with locking retainer clip enables plug conversion to C14 (connects to C13 100-250V), L6-20P (connects to L6-20R 20A 208/240V), L5-20P (connects to L5-20R 20A 120V), 5-20P (connects to 5-20R 20A 120V) and 5-15P (connects to 5-15R 15A)
- Unfiltered electrical pass-through reliably distributes AC power from UPS or generator to supported equipment
- Back panel grounding lug
- 16A circuit breaker

Specifications

OVERVIEW

Model Type	Basic
SYSTEM OVERVIEW	
Voltage compatibility (VAC)	100-250
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	100-250V
Overload protection	16A
Outlet quantity / type	12 IEC-C13 & 2 IEC-C19
INPUT	
Recommended Electrical Service	100V, 120V, 208V, 230V, 240V
Maximum Input Amps (A)	16
Input connection type	IEC-C14, NEMA L6-20P, NEMA L5-20P, NEMA 5-20P & NEMA 5-15P
Plug Type	IEC320-C14, NEMA L6-20P (20A 208/240V), NEMA L5-20P (20A 120V), NEMA 5-20P (20A 120V), NEMA 5-20P (20A 120V)
Input cord length (ft.)	10
Input cord length (m)	3
PHYSICAL	
Shipping weight (lbs)	3.8
Shipping weight (kg)	1.72
Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 4.25
Unit Dimensions (HWD/cm)	4.44 x 44.45 x 10.8
Shipping Dimensions (HWD/in)	2.5 x 10 x 20.25
Shipping Dimensions (HWD/cm)	6.35 x 25.4 x 52.1
Unit weight (lbs)	3.2
Unit weight (kg)	1.45
Material of construction	Sheet metal
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
Form factors supported	1U rackmount, 0U vertical mount, wallmount and under-counter mounting supported
ENVIRONMENTAL	
Relative Humidity	0-95% non condensing
CERTIFICATIONS	
Certifications	Tested to UL60950-1 (USA), CSA (Canada), CE (EU)
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	P002-002	2-ft. Power Cord (IEC-320-C14 to NEMA 5-15R)	-
Power Cables	P005-002	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	-
Power Cables	P005-006	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	-
Power Cables	P005-010	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	-
Power Cables	P032-007	7-ft. 12AWG Heavy Duty Power cord (IEC-320- C13 to IEC-320-C20	-
Power Cables	P034-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	-
Power Cables	P040-010	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-L6-20P)	-
Power Cables	P045-010	10-ft. 12AWG Heavy-Duty Power cord (IEC-320-C19 to NEMA L5-20P)	-
Power Cables	P047-002	2-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	-
Power Cables	P047-004	4-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	-
Power Cables	P047-006	6-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	-
Power Cables	P047-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	-
Power Cables	P049-010	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	-
Power Cables	P050-008	8-ft. Power cord (IEC-320-C19 to CEE 7/7 SCHUKO)	-
Power Cables	P052-008	8-ft. Power cord (IEC-320-C19 to BS1363 UK Plug)	-
Rackmount/Wallmount Kits	PDUSIDEBRKT	Enables Vertical Installation of Select 1U PDUs, Power Strips and Surge Suppressors in SmartRack Configurations	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3308.

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.