



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SRXCOOL12K

### 230V, Self-Contained Portable Air Conditioning Unit



#### Highlights

- Compact, portable, self-contained design ideal for IT, industrial, commercial and similar applications
- Quick and easy installation with louvered air director or directional cooling tube
- Window/drop ceiling kit included for extracting heat
- 12,000 BTU of cooling power
- Cools in confined spaces where facility air conditioning can't reach

#### Description

Tripp Lite's SRXCOOL12K is a new-generation air conditioner designed for supplemental area cooling, emergency cooling and off-hour cooling applications. Efficient, compact, self-contained and portable, the 230V, 50 Hz SRXCOOL12K is ideal for use in data centers, server and wiring closets, IT environments, home and small business offices, conference rooms, warehouses, entertainment centers or other venues with heat-sensitive equipment, particularly in areas that facility air conditioning can't reach. The SRXCOOL12K not only adjusts ambient room temperatures, but can also dehumidify and filter the air, providing better air quality for enhanced equipment performance with minimal noise and power consumption. The SRXCOOL12K uses environmentally friendly R410a Freon, which complies with EPA standards for 2010 and beyond, and is accepted worldwide.

Designed for quick, simple installation, the SRXCOOL12K plugs into an IEC C13 outlet with no adapter required. Both a standard louvered vent (for general room cooling) and a directional ducted cooling vent (to direct cold air where most needed) are provided. A directional exhaust duct safely removes hot air from the room. The built-in dehumidifier expels condensed water through the exhaust duct, with no need for a drain tube, drain pan or water collection tank.

The SRXCOOL12K meets the needs of the most demanding applications with 12,000 BTU of cooling power. A built-in timer enables the unit to be programmed for unattended startup and shutdown. Controls and displays are conveniently mounted on the top panel. An included window/drop ceiling kit provides multiple installation options.

#### Applications

- Supplemental cooling for confined areas where the facility HVAC is inadequate or doesn't reach at all.

#### Package Includes

- SRXCOOL12K cooling unit

- Louvered front vent
- Directional front vent
- Cold Air directional delivery tube
- Hot exhaust air removal tube
- Dropped ceiling or window heat ventilation kit.
- Warranty information
- Instruction manual

## Features

- Compact, portable, self-contained design; ideal for IT, industrial, commercial and similar applications
- Quick and easy installation with louvered air director or directional cooling tube
- Window/drop ceiling kit included for extracting heat
- 12,000 BTU of cooling power
- Cools in confined spaces where facility air conditioning can't reach
- Dehumidifies and filters air to promote more efficient equipment performance
- Built in evaporator expels condensate into the exhaust air stream meaning no drain tube, drain pan or water collection tank required
- Built-in timer for automatic unattended startup and shutdown
- Quiet operation with minimal power consumption
- Uses environmentally friendly R410a Freon
- Convenient top-mounted controls and displays
- 230V AC input, 50 Hz frequency compatibility
- Input cord has an IEC C14 plug.

## Specifications

<b>INPUT</b>	
Input cord length (ft.)	6
Input cord length (m)	1.83
<b>LEDS ALARMS &amp; SWITCHES</b>	
Front panel LEDs	Touch sensitive control panel with multiple LEDs and numerical temperature readout
<b>PHYSICAL</b>	
Shipping weight (lbs)	68
Shipping weight (kg)	30
Unit Dimensions (HWD/in)	32.6 x 12.6 x 19.75
Unit Dimensions (HWD/cm)	83 x 32 x 50
Material of construction	ABS
Form factors supported	Tower
<b>ENVIRONMENTAL</b>	
Cooling Capacity	12,000 BTU / 3.4 kW
<b>CERTIFICATIONS</b>	
Certifications	ETL UL484, CE
<b>WARRANTY</b>	
Product Warranty Period (U.S., Canada & Puerto Rico)	1 year

---

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4483](http://www.tripplite.com/en/products/model.cfm?txtModelID=4483).

---

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.