



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BC350

### BC Personal UPS System - Standby Mini-Desktop UPS

#### Highlights



- 350VA ultra-compact UPS
- Maintains 120V nominal output during blackouts
- Basic power-only UPS with status LEDs
- Space saving right-angle input plug
- Input: NEMA 5-15P (120V 15A) / Output: 6 NEMA 5-15R (120V)
- 3 year product warranty / \$100,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's BC350 standby UPS offers power protection for PCs, workstations and other sensitive electronics in an attractive space saving, ultra-compact housing. Prevents data loss and system downtime by providing battery-supported AC output during brownouts and blackout conditions. 6 widely spaced output receptacles accommodate large transformer plugs without blocking outlets. 3 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power; 3 additional surge suppression-only outlets are ideal for printers and other accessories not requiring battery support. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 350VA/180W power handling ability supports entry-level PCs for up to 12 min. during power failures. 3-year warranty; \$100,000 [connected equipment insurance](#) (USA, Puerto Rico, & Canada Only).

#### Package Includes

- BC350 UPS System
- Instruction manual with warranty information

#### Features

- BC350 standby UPS offers complete protection from blackouts, brownouts and surges
- 6 widely spaced outlets accommodate large transformer plugs without blocking outlets
- 3 battery-supported outlets protect computer, monitor and vital system peripherals; 3 additional surge suppression-only outlets protect printers and other system accessories not requiring battery support
- Space saving right-angle input plug
- Provides battery-derived AC output during blackouts and brownouts
- 350VA/180W power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports entry-level PC systems up to 12 min. during blackout conditions
- Space-saving, ultra-compact housing fits almost anywhere

#### Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	350

<b>Output Watt Capacity (watts)</b>	180
<b>Nominal Output Voltage(s) Supported</b>	115V; 120V
<b>Frequency compatibility</b>	60 Hz
<b>Output voltage regulation (Battery mode)</b>	115V (+/- 5%)
<b>Built-in UPS output receptacles</b>	6 5-15R outlet(s)
<b>Surge suppression only outlets</b>	3 UPS outlets, 3 surge-only outlets
<b>Output AC waveform (AC mode)</b>	Sine wave
<b>Output AC waveform (battery mode)</b>	PWM sine wave
<b>INPUT</b>	
<b>Rated input current (at maximum load)</b>	12A
<b>Nominal Input Voltage(s) Supported</b>	120V AC
<b>UPS input connection type</b>	5-15P; Space saving right angled input plug
<b>UPS Input cord length (ft.)</b>	6
<b>UPS Input cord length (m)</b>	1.8
<b>Recommended Electrical Service</b>	15A 120V
<b>BATTERY</b>	
<b>Full load runtime (minutes)</b>	2.5 min. (180w)
<b>Half load runtime (minutes)</b>	10 min. (90w)
<b>DC system voltage (VDC)</b>	12
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>LED Indicators</b>	2 LEDs indicate power status and overload/check battery status
<b>Alarms</b>	Audible alarm indicates power-failure and overload status
<b>Switches</b>	Combination switch controls on/off power status and self-test operation
<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression joule rating</b>	380
<b>UPS AC suppression response time</b>	Instantaneous
<b>EMI / RFI AC noise suppression</b>	Yes

<b>PHYSICAL</b>	
Installation form factors supported with included accessories	Tower; Ultra-compact desktop
Primary form factor	Desktop
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	3 x 10.5 x 5
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	7.6 x 26.7 x 12.7
UPS / Power Module weight (lbs)	7.7
UPS / Power Module weight (kg)	3.5
UPS Shipping dimensions (height x width x depth / inches)	4.5 x 12.5 x 7.8
UPS Shipping dimensions (height x width x depth / cm)	11.4 x 31.8 x 19.7
Shipping weight (lbs)	10
Shipping weight (kg)	4.5
UPS housing material	ABS
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	39.1
Battery mode BTU / hr. (full load)	53.2
<b>LINE / BATTERY TRANSFER</b>	
Transfer time	2-4 milliseconds
Low voltage transfer to battery power (setpoint)	99
High voltage transfer to battery power (setpoint)	139
<b>SPECIAL FEATURES</b>	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
Green & high efficiency features	Greater than 95% efficiency - GREEN UPS

CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI); ROHS (Reduction of Hazardous Substances)
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	3 years
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 connected equipment insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Audio Cables	<a href="#">CT120</a>	Instant-Read- AC Outlet Circuit Tester	-
Surge Protectors	<a href="#">DNET1</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Extended Warranties	<a href="#">WEXT5-INTERNET</a>	5-Year Extended Warranty - For Internet Office, AVR and ECO Series UPS Systems	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3065](http://www.tripplite.com/en/products/model.cfm?txtModelID=3065).

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.