



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SMART2200SLT

### SmartPro Tower UPS System - Intelligent line-interactive network power management system



#### Highlights

- 2200VA / 2.2kVA line interactive tower UPS
- Maintains sine-wave 120V nominal output over an input range of 83 to 145V
- Network communications supported via HID enabled USB port, RS-232 enabled DB9 port, SNMP/Web card slot and EPO interface
- Current monitoring via front panel meter
- Input: NEMA 5-20P (120V 20A) / Output: 6 x NEMA 5-15/20R, 1 x L5-20R (120V)
- 2-year warranty; \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

#### Description

2200VA line-interactive tower UPS system for server, networking and telecommunications equipment. Upright tower form factor. Offers sine wave 120V nominal output in both AC and battery modes. Switches to battery-derived AC output during power failures and extreme voltage variations. Line-interactive automatic voltage regulation (AVR) provides voltage boost/cut during brownouts/overvoltages to maintain regulated 120V nominal output over an input voltage range of 83-145V. Includes NEMA 5-20P input plug and 7 UPS-supported (6 x 5-15/20R & 1 L5-20R) output receptacles. Network-grade AC surge and noise suppression. Network management interfaces support simultaneous communications via USB port, DB9 serial port and SNMPWEBCARD slot. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all three network interfaces. Includes PowerAlert power management software and complete cabling. Three-stage metered current monitoring and battery charge status LEDs. Utility power and voltage regulation, and battery warning LEDs. Audible alarm. Self-test. Field-replaceable, hot-swappable internal batteries. Attractive all-black color scheme. 2-year warranty and \$250,000 [connected equipment insurance](#); extended warranty and service contracts available.

#### Package Includes

- SMART2200SLT UPS System
- PowerAlert Software and cabling
- Owner's manual with warranty information
- 

#### Features

- SmartPro line-interactive UPS system is ideal for voice, data, medical and industrial networking applications
- Line-interactive voltage regulation maintains selectable 120V nominal output during brownouts as low as 83V and overvoltages to 145V
- Enables continuous operation through blackouts, voltage fluctuations and surges
- Line-interactive automatic voltage regulation (AVR) provides 12% and 24% voltage boost during brownouts and a 12% voltage cut during overvoltages
- Standard internal battery set offers 13 min. runtime at half load (800W) and 5 min. at full load (1600W)
- Space-saving upright tower format
- Network interfaces support simultaneous communications via built-in USB port, DB9 serial port and SNMPWEBCARD slot
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Included PowerAlert power management software supports safe unattended shutdown, monitoring and control via local connected servers,

plus any number of additional servers over IP

- UPS interface supports on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, timed inverter shutoff, activate self-test and output power control
- NEMA 5-20P input plug/6 x NEMA 5-15R and 1 x NEMA L5-20R output receptacles
- Front panel LEDs provide current monitoring, voltage regulation, battery charge level, and battery warning information
- UPS ships fully assembled in full compliance with DOT regulations; no time-consuming connection of internal batteries by user required
- 2-year product warranty; \$250,000 [Ultimate Lifetime Insurance](#)

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	2200
Output kVA capacity (kVA)	2.2
Output Watt Capacity (watts)	1600
Output kW capacity	1.6
Output power factor	0.7
Nominal Output Voltage(s) Supported	120V
Frequency compatibility	60 Hz
Output voltage regulation (line mode)	-18% / +8%
Output voltage regulation (Battery mode)	+/- 5%
Built-in UPS output receptacles	6 5-15/20R outlet(s); 1 L5-20R outlet(s)
Basic PDU options	<a href="#">PDU40TDUAL</a> (0U / 40 5-15/20R outlets); <a href="#">PDU40TDUAL</a> (0U / 40 5-15/20R outlets)
Metered PDU options	<a href="#">PDUMH20</a> (1U / 13 5-15/20R outlets); <a href="#">PDUMH20AT</a> (1U / 16 5-15/20R outlets)*; <a href="#">PDUMV20</a> (0U / 16 5-15/20R outlets); <a href="#">PDUMV40</a> (0U / 32 5-15/20R outlets)
Switched PDU options	<a href="#">PDUMH20ATNET</a> (1U / 16 5-15/20R outlets)*; <a href="#">PDUMV20NET</a> (0U / 24 5-15/20R outlets)
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Sine wave
INPUT	
Rated input current (at maximum load)	14.8A
Nominal Input Voltage(s) Supported	120V AC
UPS input connection type	5-20P
Input circuit breaker	20A
UPS Input cord length (ft.)	10

UPS Input cord length (m)	3
Recommended Electrical Service	20A 120V
<b>BATTERY</b>	
Full load runtime (minutes)	5 min. (1600w)
Half load runtime (minutes)	13 min. (800w)
DC system voltage (VDC)	48
Battery recharge rate (included batteries)	Less than 4.5 hours from 10% to 90%
Replacement battery cartridge (internal UPS battery replacement)	<a href="#">RBC54</a>
Battery Access	Battery access door
Battery replacement description	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
Voltage regulation description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 83V to overvoltages to 145V
Overvoltage correction	Input voltages between 127 and 145 are reduced by 12%
Undervoltage correction	Input voltages between 96 and 108V are boosted by 12%
Severe undervoltage correction	Input voltages between 83 and 95V are boosted by 24%
<b>LEDS ALARMS &amp; SWITCHES</b>	
LED Indicators	9 LEDs indicate line power, battery power, AVR, overload and replace battery status - with a 3-LED level meter for load and battery charge level
Alarms	Audible alarm indicates power failure and overload conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC suppression joule rating	570
UPS AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
<b>PHYSICAL</b>	
Installation form factors supported with included accessories	Tower
Primary form factor	Tower

<b>UPS / Power Module dimensions in primary form factor (height x width x depth / inches)</b>	10.50 x 8.88 x 12.50
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / cm)</b>	26.67 x 22.54 x 31.75
<b>UPS / Power Module weight (lbs)</b>	57
<b>UPS / Power Module weight (kg)</b>	25.9
<b>UPS Shipping dimensions (height x width x depth / inches)</b>	14.50 x 13.75 x 18.00
<b>UPS Shipping dimensions (height x width x depth / cm)</b>	36.83 x 34.93 x 45.72
<b>Shipping weight (kg)</b>	0
<b>UPS housing material</b>	Steel
<b>Cooling method</b>	Fan
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature Range</b>	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
<b>Storage Temperature Range</b>	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
<b>Relative Humidity</b>	0 to 95%, non-condensing
<b>AC mode BTU / hr. (full load)</b>	286.3
<b>Battery mode BTU / hr. (full load)</b>	885.6
<b>Audible Noise</b>	Audible Noise < 50 dBA at Front Side 1 Meter
<b>COMMUNICATIONS</b>	
<b>Communications interface</b>	USB; DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface
<b>Network monitoring port description</b>	Supports detailed monitoring of UPS and site power conditions
<b>PowerAlert software</b>	Included
<b>Communications cable</b>	USB and DB9 cabling included
<b>WatchDog compatibility</b>	Supports Watchdog application, OS and hard-reboot restart options for remote applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time</b>	2-4 milliseconds
<b>Low voltage transfer to battery power (setpoint)</b>	83
<b>High voltage transfer to battery power (setpoint)</b>	145

<b>SPECIAL FEATURES</b>	
<b>Cold Start (startup in battery mode during a power failure)</b>	Cold-start operation supported
<b>High availability UPS features</b>	Hot swappable batteries
<b>Green &amp; high efficiency features</b>	Greater than 95% efficiency - GREEN UPS
<b>CERTIFICATIONS</b>	
<b>UPS Certifications</b>	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI); ROHS (Reduction of Hazardous Substances)
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2 years
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$250,000 connected equipment insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Power Distribution	<a href="#">PDU1215</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
Power Distribution	<a href="#">PDUNV</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
SNMP Accessories	<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	-
SNMP Accessories	<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	-
USB Hubs/Accessories	<a href="#">U022-010</a>	10-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	-
Software	<a href="#">WATCHDOGSW</a>	WatchDog Service Monitoring / Reboot Software	-
Surge Protectors	<a href="#">DNET1</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Surge Protectors	<a href="#">DTEL2</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Extended Warranties	<a href="#">WEXT3-2200-3000</a>	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA	-
Extended Warranties	<a href="#">WEXT5-2200-3000</a>	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 2200-3000VA or less	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3489](http://www.tripplite.com/en/products/model.cfm?txtModelID=3489).