GL480E-2432



Enhanced Series Enclosures

SHIPPING WEIGHT: 200 lbs.

DIMENSIONS: 48.00"H x 24.00"W x 32.00"D

Usable inside depth: 30"

RACK SPACES: 24 RMU 19" EIA 310-D Compliant

STOCK COLORS: Black, Advantage Gray, or Nitro Blue

WEIGHT CAPACITY: 600 lbs.

ULLISTED: UL60950-1 Standard for IT &

Communications Equipment, Cabinet Enclosures and Rack Systems



GL480E-2432 Series Enclosures

PART NO.	DESCRIPTION
4801E-2432	Base unit with two (2) pair of black powder coated universal 19" mounting rails (M6) and package of M6 hardware
7209-N	Adjustable levelers (2.50" in height) - set of 4*
TPE-24L	Removable louvered top with two 4.00" horseshoe knock-outs
4802E-24	Plexiglas door with locking swing handle
4804E-24	Perimeter vented steel rear door with locking swing handle
4810-32ELS	Pair of solid lift-off side panels w/lock & finger release latches
7218-24	8 position power strip with circuit breaker and 15 ft. cord
GL480E-2432L	Complete enclosure with TPE-24L louvered top
GL480E-2432F	Complete enclosure with TPE-24F fan top
GL480E-2432F10	Complete enclosure with TPE-24F10 fan top
GL480E-2432S	Complete enclosure with TPE-24S solid top

GL480E-2432

Most Popular Accessories for the GL480E-2432

PART NO. DESCRIPTION

DOORS & SIDE PANELS

4803E-24 Solid door 4802E-M24 Mesh door

4811-32ELL Pair of removable fully louvered side panels

Additional Doors, Page 48

REMOVABLE TOP & BOTTOM PANELS

TPE-24F Top panel & fan assembly w/two 4.00" horseshoe knock-outs TPE-24S Solid top panel w/two 4.00" horseshoe knock-outs

BP-ES Bottom panel, solid
BP-EF Bottom panel, filtered

Additional Tops & Bottom Panels, Page 50

STATIONARY SHELVES FOR 19" MOUNTING

7206-FM Stationary front mount shelf – 17.25"W x 18.00"D Front & rear mount, adjustable – 17.50"W x 22.25"D Front & rear mount, adjustable – 17.50"W x 27.25"D Front & rear mount, adjustable – 17.50"W x 28.00"D Front & rear mount, adjustable – 17.50"W x 28.00"D

Additional Shelves & Shelf Weight Capacities, Page 52

SLIDING SHELVES FOR 19" MOUNTING

7206-SL Sliding shelf – 16.343"W x 17.50"D
7206-FRSL-AHD Front & rear mount sliding, adjustable – 17.50"W x 22.00"D
7206-FRSL-ADT Front & rear mount sliding, adjustable – 17.50"W x 26.00"D
7206-PKB-MT Pivoting keyboard tray with mouse tray – 20.625"W x 9.50"D

Additional Shelves & Shelf Weight Capacities, Page 52

19" RACK MOUNT CABLE MANAGEMENT

CM-05 Single-sided cable organizer, 1 RMU CM-09 2-sided cable organizer, 1 RMU

CM-01 Cinch strap - 12"L x 3/4" W w/buckle and grommet CM-06 Cinch strap - 6"L x 3/4" W w/buckle and grommet

Additional Cable Management, Pages 54-55

POWER OUTLET STRIPS, COPPER BUS BARS & COOLING EQUIPMENT

7217FT Fan tray with three 75 CFM fans

7217FT-3 Front and rear mount, adjustable fan tray w/three 75 CFM fans

for 19" mounting

14 position (6 front/8 back) power strip with circuit breaker

& surge suppressor for 19" mounting

CBB-48 Copper bus bar, 45.75" (isolated)

Additional Power Outlet Strips, Page 53

CASTERS, LEVELERS, MOUNTING RAILS & NETWORKING HARDWARE

4805E2P Pair of mounting rails to accept M6 cage nuts w/hardware HDW-105-50 Package of 50 M6 cage nuts w/screws - 12mm screw length Networking hardware allows ganging of enclosures Casters – one set of four (2 locking and 2 non-locking) Adjustable levelers (4.00" in height) – one set of four

* When casters & levelers are used together, 4" levelers are required. Additional Accessories, Pages 48-58