

GL840E-2432



Enhanced Series
Enclosures

Enhanced Series Enclosures

SHIPPING WEIGHT: 350 lbs.

DIMENSIONS: 84.00"H x 24.00"W x 32.00"D
Usable inside depth: 30"

RACK SPACES: 44 RMU 19" EIA 310-D Compliant

STOCK COLORS: Black, Advantage Gray, or Nitro Blue

WEIGHT CAPACITY: 1500 lbs. on levelers, bolted to floor, or
on heavy duty casters (part no. 7208-EHD)

UL LISTED: UL60950-1 Standard for IT &
Communications Equipment, Cabinet
Enclosures and Rack Systems



GL840E-2432 Series Enclosures

PART NO.	DESCRIPTION
8401E-2432	Base unit with two (2) pair of powder coated 19" universal (M6) rails and M6 hardware
7209-N	Adjustable levelers (2.50" in height) - set of 4*
TPE-24L	Removable louvered top panel w/two 4.00" horseshoe knock-outs
8402E-24	Plexiglas door with locking swing handle
8404E-24	Perimeter vented steel rear door with locking swing handle
8410-32ELS	Pair of solid lift-off side panels w/lock and finger release latches
7215	16 position power strip with circuit breaker and 15 ft. cord
GL840E-2432L	Complete enclosure with TPE-24L louvered top
GL840E-2432F	Complete enclosure with TPE-24F fan top
GL840E-2432F10	Complete enclosure with TPE-24F10 fan top
GL840E-2432S	Complete enclosure with TPE-24S solid top

GL840E-2432

Most Popular Accessories for the GL840E-2432

PART NO. DESCRIPTION

DOORS & SIDE PANELS

8402E-24PV	Perimeter vented plexiglas door
8403E-24	Solid door
8402E-M24	Mesh steel door
8411-32ELL	Pair locking lift-off louvered side panels

Additional Doors & Side Panels, Pages 48-49

REMOVABLE TOP & BOTTOM PANELS

TPE-24F	Top panel & fan assembly w/two 4.00" horseshoe knock-outs
TPE-24F10	Top panel & fan assembly w/550 CFM 10" fan & 6 ft. cord
BPF24	Bottom Panel, Filtered, 13"W x 16"D w/rear solid panel for 24"W enclosure
BPS24	Bottom Panel, Solid, 13"W x 16"D w/rear solid panel for 24"W enclosure

Additional Tops & Bottom Panels, Page 50

CABLE MANAGEMENT

VLB-8432	Vertical lacing bar kit (includes 1 vertical lacing bar, 2 horizontal lacing bars and 6 CM-01 cinch straps)
HLB-32	Horizontal lacing bar - 32" deep
VLB-84	Extra vertical lacing bar - to be used with lacing bar kit (includes 6 CM-01 cinch straps)

19" RACK MOUNT CABLE MANAGEMENT

CM-04	Interbay cable organizer, 2 RMU
CM-08	Standard front cable organizer, 2 RMU

Additional Cable Management, Pages 54-55

STATIONARY SHELVES FOR 19" MOUNTING

7206-FR-AHD	Front & rear mount, adjustable – 22.25"D, 200 lb. weight cap.
7206-FR-ADHD	Front & rear mount, adjustable – 27.25"D, 150 lb. weight cap.
7206-FR-A28HD	Front & rear mount, adjustable – 28.00"D, 300 lb. weight cap.

Additional Shelves & Shelf Weight Capacities, Page 52

SLIDING SHELVES FOR 19" MOUNTING

7206-FRSL-AHD	Front & rear mount sliding, adjustable – 22.00"D, 110 lb. weight cap.
7206-FRSL-ADHD	Front & rear mount sliding, adjustable – 26.00"D, 110 lb. weight cap.

Additional Shelves & Shelf Weight Capacities, Page 52

SPECIALTY SHELVES FOR 19" MOUNTING

7206-MKM	Monitor/keyboard/mouse shelf
7206-PKB-MT	Pivoting keyboard tray with mouse tray

POWER OUTLET STRIPS, COPPER BUS BARS & COOLING EQUIPMENT

7215-S	16 position power strip w/surge suppressor & 5-15P plug
7215-20ARTLP	20 amp, 16 position power strip w/circuit breaker & twist lock L5-20P plug
7215-20AR	20 amp, 16 position power strip w/circuit breaker & 5-20P plug
CBB-72	Copper bus bar 70" (isolated)
7217FT-3	Front & rear mount, adjustable fan tray w/three 75 CFM fans

Additional Cooling Equipment, Page 54 Additional Power Outlet Strips, Page 53

CASTERS, LEVELERS, MOUNTING RAILS & OTHER ACCESSORIES

8405-ES1P	Pair of 19" EIA mounting rails, tapped 10/32 w/hardware
8405-ES2P	Pair of 19" EIA mounting rails to accept M6 cage nuts w/hardware
HDW-105-50	Package of 50 M6 cage nuts w/screws - 12mm screw length
AT2	Anti-tip legs
G101	Networking/Ganging kit
AK101	Seismic anchoring kit
7208-E	Casters – one set of four (2 locking and 2 non-locking)
7208-EHD	Heavy Duty Casters – one set of four (all 4 locking) - weight cap. 1500 lbs.
7209-N4	Adjustable levelers (4.00" in height) – one set of four

** When casters & levelers are used together, 4" levelers are required.*

Additional Accessories, Pages 48-58