

■ Integrated Cabinet Solutions  
For *Business-Critical Continuity™*

*Liebert® MCR*  
*Mini Computer Room Enclosure*



# Liebert MCR

## Mini Computer Room Enclosure

The Liebert MCR is a self-contained rack enclosure system that includes a load-sized, computer-grade air conditioner located at the bottom of the enclosure, with the option of a top mount design, supplying cool air to sensitive equipment on all levels. A back-up cooling system ensures environmental security. Power can be supplied and protected through an optional Liebert GXT on-line UPS or Liebert PSI line-interactive UPS.



An optional top mounted ECM allows for maximum use of internal rack space and can be used to double capacity with internal/rack mount ECM.

**Secure Door lockable door** provides an extra measure of security by limiting access to critical equipment.

**BCM**  
(Back-up Cooling Module)


**Sealed Door**  
specially designed rubber gasket provides NEMA12 sealing protection.

**Liebert GXT2**  
on-line UPS

**ECM**  
(Environmental Control Module)



## Exclusive Uninterruptible Environmental Support




### Internal ECM

The integrated ECM enclosure design promotes the best air circulation to prevent hot spots within the enclosure. Inside and outside air are isolated for maximum cleanliness.




### Back-Up Cooling

During high internal temperature or power outage conditions, the BCM (Back-Up Cooling Module) — powered by the enclosure's UPS — is automatically activated, drawing in filtered outside air to ensure continuous air flow to protected equipment.



### Air Distribution

Exclusive ECM conditioned air distribution duct ensures uniform air flow for multiple enclosures.



### External ECM

The top mounted ECM allows maximum use of internal rack space or can be used with the internal/rack mount ECM to double cooling capacity.

### Flexibility:

- Designed as a plug-and-play system ready to install.
- Wheel-mounted cabinet for easy relocation.
- Adjustable racks and rack rails support a wide variety of equipment.
- Optional top mounted air conditioning allows maximum use of internal rack space or can be used to double cooling capacity with the internal air conditioning unit.

### Higher Availability:

- Cools IT equipment to eliminate downtime from overheating.
- Lockable door protects against unauthorized access.
- Specially designed door gasket and sealed cable entrance ensure stable cooling environment.
- Back-up cooling assures continued cooling in the event of a power loss.
- Improved cable access and management improves airflow to reduce overheating of protected IT equipment.

### Lowest Total Cost Of Ownership:

- Competitively priced as an integrated system, compared to purchasing separate components.
- Simplified plug-and-play installation reduces overall implementation time, reducing costs.
- Optional energy saver control saves money by allowing back-up cooling to operate as primary enclosure cooler.
- Integrated air conditioning reduces potential downtime costs by assuring proper system operation.

### Ideally Suited For:

- Network closets
- Server closets or small rooms

Liebert MCR  
22U Model



# Ensuring The High Availability Of Mission-Critical Data And Applications.

## Specifications

### ENCLOSURE DIMENSIONS

Model	Overall Frame Dimensions			Rack		Adjustable Rack Depth		Internal Rack Height	
	Height*	Width	Depth***	Width	Available Width	B****		RACK U	In. (mm)
	In. (mm)			In. (mm)	In. (mm)	Max In.(mm)	Min In.(mm)		
HD_780	77 (1956)	23.5 (597)	30 (762)	19 (483)	17.8 (450)	22.5 (571.5)	18.5 (470)	42	73.5 (1867)
HD_788	77 (1956)	23.5 (597)	38 (965)	19 (483)	17.8 (450)	30.5 (775)	26.5 (673)	42	73.5 (1867)

\* Casters add 1.5" to overall height of frame = 2000mm.

\*\*\* BCM option adds an additional 3.00" to overall depth of frame.

\*\*\*\* Max dimension is for ex-factory configuration. Rails can be inverted to provide an additional 4.00" of adjustment.

### ECM (Environmental Cooling Module) PERFORMANCE DATA

Model Number	Rated Capacity	Supported Load	Max Ambient	Height	Width	Depth	Total Heat Rej.	Input Power (1PH)					Plug	Sound Lpa (1.5 m)
	BTUH (Watts)	BTUH (Watts)		In (mm) - U	In (mm)	In (mm)	BTUH (Watts)	Volts	Hz	FLA	WSA	OPD		
ECM2000L*-C60	6897 (2021)	5621 (1647)	105°F / 41°C	12.25 (311)-7	17.43 (443)	29 (737)	10935 (3204)	120	60	9.8	11.7	15	73.5 (1867)	52

\*\* T (top mount) and R (rack mount). Top mount weight does not include interface plenum. The interface plenum for a 19" rack x 30" deep cabinet is 38 lbs."

Sound data based on sound pressure A- weighted scale for free field spherical radiation at 1.5 meters from cabinet.

Sound data reflects only rack mount design. Consult factory for top mount data.

### BCM (Back-Up Cooling Module) PERFORMANCE DATA

Model Number	Rated Capacity	Supported Load	Max Ambient	Height	Width	Depth	Weight	Total Heat Rej.	Input Power (1PH)					Sound Lpa (1.5 m)
	BTUH (Watts)	BTUH (Watts)		In (mm) - U	In (mm)	In (mm)	lbs (kg)	BTUH (Watts)	Volts	Hz	FLA	WSA	OPD	
BCM 2000L-60	N/A	2811 (824)	105°F / 41°C	35.0 (889)	15.5 (393.7)	3.75 (95.2)	47 (21.3)	10935 (3204)	120	60	2.0	2.5	15	59

Above BCM weight includes rear door weight of 17 lbs.

Sound data based on sound pressure A- weighted scale for free field spherical radiation at 1.5 meters from cabinet.

### 22U PACKAGED ENCLOSURE

Model	Overall Frame Dimensions in. (mm)			Rack in. (mm)		Adjustable Rack Depth in. (mm)		Internal Rack Height		Weight	Rack Cooling supported load
	Height	Width	Depth	Width	Available Width	Maximum	Minimum	Rack U	In. (mm)		
HD448D000KD945 (rack and cooling module)	59.1 (1501)	23.5 (597)	38 (965)	19 (483)	17.8 (450)	30.5 (775)	26.5 (673)	22	38.5 (978)	367	1647 Watt
HD448D0C0KE865 (rack, cooling module, 2000VA Liebert GXT3 UPS, Liebert MPH Rack PDU)	59.1 (1501)	23.5 (597)	38 (965)	19 (483)	17.8 (450)	30.5 (775)	26.5 (673)	22	38.5 (978)	441	1647 Watt

22U Model dimensions include top-mount module and casters

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2009 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice.













All names referred to are trademarks or registered trademarks of their respective owners.

© Liebert is a registered trademark of the Liebert Corporation.

SL-15602 (R12/09) Printed in USA

## Emerson Network Power.

The global leader in enabling *Business-Critical Continuity™*.

-  AC Power
-  Embedded Computing
-  Outside Plant
-  Racks & Integrated Cabinets
-  Connectivity
-  Embedded Power
-  Power Switching & Controls
-  Services
-  DC Power
-  Monitoring
-  Precision Cooling
-  Surge Protection

*Business-Critical Continuity*, Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.  
©2009 Emerson Electric Co.