

# GLRR-1984BA and GLRR-1984

Racks



## 19" Open Bay **Relay Rack**

**SHIPPING WEIGHT:** 30 lbs. (1 Package)

**DIMENSIONS** 84.00"H x 20.31"W x 14.00"D  
45 RMU  
Weight Capacity: 750 lbs.

**EXTRUDED ALUMINUM:** Double Sided  
12-24 Tapped Holes  
19" EIA 310-D Compliant Mtg.

**FINISH:** GLRR-1984 - Anodized  
GLRR-1984BA - Black Anodized

**UL LISTED:** UL60950-1 Standard for IT &  
Communications Equipment, Cabinet  
Enclosures and Rack Systems



GLRR-1984BA

### GLRR-1984BA and GLRR-1984 Open Bay Relay Racks


#### DESCRIPTION

Rack component part list: (2) vertical uprights, (2) base angles, (2) top angles, (12) 1/2"– 13 x 1 hexhead bolts & (12) 1/2" lock washers, (50) 12-24 x 1/2" mounting screws

PART NO.	FINISH
GLRR-1984BA	Black anodized finish
GLRR-1984	Anodized finish

*NOTE: Other Heights are available, contact your Great Lakes Representative for more information.*

#### ACCESSORIES

7219	6 position power strip with circuit breaker and 15 ft. cord for 19" mounting
 7219-SR14	14 position (6 front, 8 back) power strip with circuit breaker and surge suppressor for 19" mounting
19SRB	Strain relief bar

#### SHELVES FOR 19" MOUNTING

7206-EIA	Stationary shelf – 17.468"W x 18.00"D
7206-SL	Sliding shelf – 16.343"W x 17.50"D
7206-FM	Stationary front mount shelf – 17.25"W x 18.00"D
7206-14	Stationary shelf – 17.50"W x 14.00"D
1984ST09	Single-sided 9" deep HD shelf (see page 15)
1984ST15	Single-sided 15" deep HD shelf (see page 15)