

Liebert FPC
Packaged Power Distribution For Today's Rack-Based Data Centers And IT Facilities





Creating high quality power is a major step towards protecting the operation of a critical facility. But don't stop there. Once you've created a better level of power, you need to make sure that it can be distributed properly to each and every piece of important equipment.

The Liebert Packaged Power Distribution Solution For Growing IT Operations

Providing Proper Power To Each Plug

Power conditioning and distribution is an ever-important function in today's high density, rack-based data center and IT environments. Whereas in the past it was considered a simplistic solution, the exploding number of dynamic devices and dual-corded loads has elevated the criticality and visibility of power distribution.

The proper delivery of power from the UPS system to your critical load equipment is a key element of system availability. Studies show that 80% of all power-related downtime is caused by disruptions between the UPS and the critical load.

As your rack-mount systems grow in number, complexity and criticality — so must your power distribution system. To meet this challenge Liebert has created a product designed to optimize power distribution at the rack level with the “plug-and-play” flexibility that today's IT managers demand from their systems.

A Noticeable Improvement In Power Quality

The Liebert FPC power center is engineered to combine the convenience and cost savings of a pre-packaged, factory-tested unit with the flexibility of a custom-tailored power system.

Based on the proven design of the Liebert Precision Power Center, the Liebert FPC continues the tradition of critical power distribution excellence. The Liebert FPC is a self-contained system that provides:

- Power Isolation
- Power Distribution
- Computer-Grade Grounding
- Power Monitoring

The system utilizes the standard size and appearance of the Liebert Foundation™ enclosure to address the physical needs of today's IT requirements. The Foundation-style enclosure enables these units to be used as part of a rack enclosure grouping, as well as in standalone applications.



The Liebert FPC power center can be used in conjunction with several Liebert FDC distribution units to create a total power distribution system for high density racks.

Managed Power Solutions

The Liebert FPC power center is part of the Liebert MP Product Family - a group of power distribution and switching systems designed to manage power from the UPS all the way to each individual piece of computing and communications hardware. Liebert believes you can't get to “high 9's” reliability with a good UPS alone. You need a total high availability power distribution solution to reach that level of performance.



The Liebert FPC

The Liebert FPC is designed to bring you a distribution system that will close the power delivery loop in your critical IT operations.

The Liebert FPC features a compact, space saving design, flexible breaker configurations, plus local and remote power monitoring capabilities. Available in capacities from 15 kVA up to a new 300 kVA system, the Liebert FPC offers flexibility to fit both the space and electrical requirements of IT equipment.

Other features and enhancements make Liebert FPC the right choice to protect sensitive electronics in growing sites.



A Proven System

The packaged system approach of the Liebert FPC is convenient and space-saving, reducing installation time and cost compared to a conventional approach using multiple interconnected components. The Liebert FPC is built on a proven system design used in thousands of installations, and unlike one-of-a-kind, built-up distribution arrangements constructed at the site, it undergoes thorough factory testing as a complete system to assure reliable, consistent performance.

There are a number of integral features that enable the Liebert FPC to offer a higher quality level of electrical power for your critical applications:

- **Computer-Grade Grounding** — The Liebert FPC automatically establishes a single point ground to meet major manufacturers' recommendations and the requirements of the National Electric Code.
- **Handles Non-Linear Loads** — Fully compatible with the non-linear loads of modern computer systems and other electronic equipment.
- **Main Input Breaker With Shunt Trip** — provides primary transformer overcurrent protection, a power disconnecting means and a method to interface with shutdown controls.
- **A Double-Shielded Isolation Transformer** — located close to the load provides superior noise attenuation.
- **One Or More Individually Enclosed 42-Pole Output Panelboards** — with main breaker and individual isolated neutral and ground bus bars distribute power to the sensitive load equipment.
- **Monitoring** — Built-in metering and alarm annunciation with communication to Liebert centralized monitoring.
- **Space Savings** — Compact single cabinet conserves valuable floor space.
- **Easy Installation** — Single input cable connection reduces installation time and cost.
- **Full Front And Rear Access** — with removable doors and panels, bottom or top cable entry/exit.
- **Location Flexibility** — The unit can be easily relocated to protect your investment.
- **UL and ULC Listed as a Complete System** — Meets safety requirements for fast, hassle-free inspection and building code approvals.

Optional Features Include:

- Remote emergency power off (EPO) switch.
- Subfeed breakers, up to three 225A or 400A on 150-300 kVA.
- Square D bolt-in or plug-in inline panelboards.
- GE bolt-in or plug-in inline panelboards.
- Low voltage control junction box with cable.
- Lightning/surge arrester.
- Output surge suppression module.
- Liebert Accuvar transient voltage surge suppressor.
- K-factor transformer.
- Isolated ground bus bars.
- 22kAIC panelboard mains.
- Liebert NIC (network interface card).
- EZ-View or solid doors.
- Side panels.
- Branch circuit monitoring.



Ensuring The High Availability Of Mission-Critical Data And Applications.

Liebert FPC Specifications

Two Enclosure Sizes
15-125 kVA - housed in 19" rack, 23.5"W x 38"D x 78.5"H
150-300 kVA - housed in space of two 19" rack, 47"W x 38"D x 78.5"H
Capacity Ratings
15, 30, 50, 75, 100, 125, 150, 200, 225, 300 kVA
Voltages
Input - 208, 380, 400, 415, 480, 600V
Output - 208/120V, 380/220V, 400/230V, 415/240V
Frequency
50 or 60 Hz
Enclosure
Color - Black
Doors - Removable front and back (same doors as offered with Liebert Foundation enclosure)
Removable cable plates, cables can be routed through the bottom of the racks
Casters and leveling feet
Convection cooled up to 225 kVA
Access - Front and rear only
Removable input and output cable trays
Panelboards
15-125 kVA - 2 panelboards
150-300 kVA - 4 panelboards
150-300 kVA - Square D I-Line panelboard
Monitoring
PMP (Power Monitoring Panel) - Display will be mounted on the unit but can be operated without opening the door, door can be easily removed

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2006 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice.

All names referred to are trademarks or registered trademarks of their respective owners.

© Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

SL-20410 (R08/06) Printed in USA

Emerson Network Power.

The global leader in enabling Business-Critical Continuity™.

- AC Power Systems
- Embedded Computing
- Outside Plant
- Services
- Connectivity
- Embedded Power
- Power Switching & Control
- Site Monitoring
- DC Power Systems
- Integrated Cabinet Solutions
- Precision Cooling
- Surge Protection

Business-Critical Continuity, Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
©2006 Emerson Electric Co.