

Specifically designed for use with rack-mounted equipment and the A740 Rack Locator, these affordable and easy to install IR-enabled tags allow you to instantly determine and verify the location of rack-based IT assets.

Features & Benefits

- ◆ **Encoded Radio Transmissions at 433 MHz**
- ◆ **Specially Designed for Use with U-Mounted, Rack Installed Assets**
- ◆ **Designed for Use with a Single Asset**
- ◆ **Industrial-Strength Adhesive Backing Keeps Tag Securely in Place**
- ◆ **Superior Anti-Collision Technology for High Tag Densities**
- ◆ **Designed for Use with the A740 Rack Locator**
- ◆ **Easy Installation**
- ◆ **On-Demand Inventory of Rack-Mounted Assets**
- ◆ **Low Power Consumption for Long Battery Life**

R104-i IR-Enabled Tags are equipped with on-board infrared (IR) sensors. These tags are designed to be deployed in concert with RF Code's A740 Rack Locators and A750 Room Locators. IR-enabled tags monitor their environment for incoming IR signals and periodically report both their own unique ID and IR location codes. Tagged assets can be rapidly located with rack-level or room-level precision. The R104 enclosure is injection-molded using an IR-transparent material with an integrated optic lens that synchronizes the tag with the nearest IR transmitter. Since the location is determined via the IR code, there is no need for redundant readers, signal strength calculations or triangulation algorithms.

Designed for use with rack-mounted assets, the R104-i battery-powered 433 MHz RF transmitter features an industrial-strength adhesive backing for quick and easy installation. Simply peel off the adhesive backing and attach the tags to

any standard U-mounted rack assets that need to be tracked, located and identified. The form factor of these affordable, single-use tags ensures clear signal transmission in rack and data center deployments. Every tag broadcasts its unique ID and IR location using RF Code's patented communication protocol, allowing for very high tag densities and ensuring accurate real-time collection of asset inventory and location data.

Powered by a coin cell battery, the R104-i tag will perform reliably in extreme temperature environments (from -20 to +70 degrees Celsius). In addition, the tag performs well after exposure to humidity and hot / cold cycles. R104 tag cases are impact resistant and temperature stable. The R104 tag operates with a very low duty cycle that translates to long battery life (typically > 5 years). These tags provide an economical solution for a variety of asset tracking environments.

RF Code solutions eliminate expensive, inaccurate, time-consuming manual processes while increasing visibility of your data center's rack-based assets. With RF Code, you have "instant inventory"—automated, real-time, on-demand physical asset inventory and management for your data centers.



RF Code R104-i IR-Enabled IT Asset Tag Specifications

OPERATION

Operating Frequency	433.92 MHz
Group Code & Tag ID Codes	> 540,000 unique IDs per Group Code
Typical Transmission Range	> 30 ft in the data center
Radiated Emissions	71.8 dBuV/m at 3 meters (maximum)
Modulation	ASK
Stability	Saw stabilized

ENCLOSURE

Width (tongue)	2.22 in (56.4 mm)
Depth (tongue)	4.96 in (126.0 mm)
Height (tongue, including IR lens)	0.51 in (12.9 mm)
Case Weight (with tag)	1.20 oz (34.16 g)
Construction	Lexan polycarbonate
Durability	Tough, impact resistant and temperature stable
Mounting Options	3M 200 MP Adhesive

ENVIRONMENTAL

Operating Temperature	-20° C to +70° C
Storage Temperature	-40° C to +80° C
Operating Humidity	< 95% RH non-condensing; not recommended for outdoor applications
Sealing	Splash resistant

IR COMPATIBILITY

Rack Locators	RF Code A740 with Series 2 Protocol
Room Locators	RF Code A750 with Series 2 Protocol

POWER

Battery Type	Lithium CR2032 coin cell
Smart Tag Feature	Low battery indication
Battery Life	> 5 years

