

# S<sup>2</sup> Enclosures

## S2 Series Enclosures



### Features


- Developed for the sound and security market
- Rails in the S2 enclosure are infinitely adjustable
- Welded construction
- The three door options (as well as the side panels) mount externally on the frame
- Available with three tops and horseshoe knock-outs as the E-Series
- Currently available in two sizes:  
84"H x 24"W x 32"D or 84"H x 24"W x 36"D  
(black only)
- Large open bottom with provisions to bolt to the floor
- Power strips mount vertically at any depth
- Ability to be networked with no tools required without side panels



VLB-84 vertical lacing bar



Infinitely adjustable rails



For more info on Sound & Security, see our Sentry catalog or visit our security website:

[www.werackyourworld.com/security](http://www.werackyourworld.com/security)

# GL840S2-2432



## S<sup>2</sup> Series Enclosures

**SHIPPING WEIGHT:** 275 lbs.

**DIMENSIONS:** 84.00"H x 24.00"W x 32.00"D

**RACK SPACES:** 45 RMU

**STOCK COLOR:** Black

**WEIGHT CAPACITY:** 1200 lbs.



UL60950-1 Standard for IT & Communications Equipment, Cabinet Enclosures, and Rack Systems

PART NO.	DESCRIPTION
8401S2-2432	84"H x 22.25"W x 30.375"D Base Unit with M6 rails and package of M6 hardware
7209N	Adjustable levelers (2.50"H) set of 4
8402S2-24	Plexiglas door assembly
8404S2-24	Perimeter-vented rear door
8410-32S2LS	Pair of side panels
TPS2-2432L	Vented top panel with 7217 fan provision
GL840S2-2432	Complete enclosure includes items above

Multi-Market Value!

## Most Popular Accessories for the GL840S2-2432

### PART NO. DESCRIPTION

#### DOORS

8402S2-M24 Mesh door

#### REMOVABLE TOP PANELS

TPS2-2432S Solid top, 32" deep  
 TPS2-2432F10 10" fan top for 32" deep enclosure

#### CABLE MANAGEMENT

VLB-84 Vertical lacing bar - to be used with lacing bar kit (includes 6 CM-01 cinch straps)

#### 19" RACK MOUNT CABLE MANAGEMENT

CM-04 Interbay cable organizer, 2 RMU  
 CM-05 Single-sided cable organizer, 1 RMU  
 CM-08 Standard front cable organizer, 2 RMU  
 Additional Cable Management, Pages 64-65

#### STATIONARY SHELVES FOR 19" MOUNTING

7206-FR-AHD Front & rear mount, (adj.) – 22.25"D, Wt. cap.: 200 lbs.  
 7206-FR-A28HD Front & rear mount, (adj.) – 28.00"D, Wt. cap.: 300 lbs.  
 7206-FR-ADHD Front & rear mount, (adj.) – 27.25"D, Wt. cap.: 150 lbs.  
 7206-FM Stationary shelf - 17.25"W x 18.00"D, 60 lb. weight cap.  
 Additional Shelves & Shelf Weight Capacities, Page 62

#### SLIDING SHELVES FOR 19" MOUNTING

7206-FRSL-ADHD Front & rear mount sliding, (adj.) – 26.00"D, Wt. Cap.: 110 lb.  
 7206-FRSL-AHD Front & rear mount sliding, (adj.) – 22.00"D, Wt. Cap. : 110 lb.  
 Additional Shelves & Shelf Weight Capacities, Page 62

#### SPECIALTY SHELVES FOR 19" MOUNTING

7206-MKM Monitor/keyboard/mouse shelf  
 7206-PKB-MT Pivoting keyboard tray with mouse tray

#### POWER OUTLET STRIPS, COPPER BUS BARS & COOLING EQUIPMENT

7215 16 position power strip w/circuit breaker & 5-15P plug  
 7215-20AR 16 position power strip w/circuit breaker & 5-20P plug  
 7215-20ARTLP 20 amp, 16 position power strip w/circuit breaker & twist lock L5-20P plug  
 CBB-78 Copper bus bar  
 7217 Fan assembly with three 75 CFM fans - mounts to vented top (TPS2-2432L)  
 Additional Cooling Equipment, Page 63 Additional Power Outlet Strips, Page 61, 69-72

#### CASTERS, LEVELERS, MOUNTING RAILS & OTHER ACCESSORIES

7209-N Adjustable levelers (2.50" in height) – one set of four  
 7208-E Casters – one set of four (2 locking and 2 non-locking)  
 8405S21032 Pair of 19" mounting rails, tapped 10/32 w/hardware  
 8405S2M6 Pair of 19" mounting rails to accept M6 cage nuts w/hardware  
 G101 Networking/Ganging kit  
 HDW-105-50 Package of 50 M6 cage nuts w/screws  
 1.75-FP19 Filler panel, 1.75"H for 19" rack mounting, 1 RMU  
 3.50-FP19 Filler panel, 3.50"H for 19" rack mounting, 2 RMU  
 5.25-FP19 Filler panel, 5.25"H for 19" rack mounting, 3 RMU

# GL840S2-2436



## S<sup>2</sup> Series Enclosures

**SHIPPING WEIGHT:** 300 lbs.

**DIMENSIONS:** 84.00"H x 24.00"W x 36.00"D

**RACK SPACES:** 45 RMU

**STOCK COLOR:** Black

**WEIGHT CAPACITY:** 1200 lbs.



UL60950-1 Standard for IT & Communications Equipment, Cabinet Enclosures, and Rack Systems

PART NO.	DESCRIPTION
8401S2-2436	84"H x 22.25"W x 34.375"D Base Unit with M6 rails and package of M6 hardware
7209N	Adjustable levelers (2.50"H) set of 4
8402S2-24	Plexi door assembly
8404S2-24	Perimeter-vented rear door
8410-36S2LS	Pair of side panels
TPS2-2436L	Vented top panel with 7217 fan provision
<b>GL840S2-2436</b>	<b>Complete enclosure includes items above</b>

*For more enclosures, see our Sentry catalog!*

## Most Popular Accessories for the GL840S2-2436

### PART NO. DESCRIPTION

#### DOORS

8402S2-M24 Mesh door

#### REMOVABLE TOP PANELS

TPS2-2436S Solid top, 36" deep  
TPS2-2436F10 10" fan top for 36" deep enclosure

#### CABLE MANAGEMENT

VLB-84 Vertical lacing bar - to be used with lacing bar kit (includes 6 CM-01 cinch straps)

#### 19" RACK MOUNT CABLE MANAGEMENT

CM-04 Interbay cable organizer- 2 RMU  
CM-05 Single-sided cable organizer- 1 RMU  
CM-08 Standard front cable organizer- 2 RMU  
Additional Cable Management, Pages 64-65

#### STATIONARY SHELVES FOR 19" MOUNTING

7206-FR-AHD Front & rear mount, (adj.) – 22.25"D, Wt. cap.: 200lbs.  
7206-FR-A28HD Front & rear mount, (adj.) – 28.00"D, Wt. cap.: 300lbs.  
7206-FR-ADHD Front & rear mount, (adj.) – 27.25"D, Wt. cap.: 150lbs.  
7206-FM Stationary shelf - 17.25"W x 18.00"D, 60 lb. weight cap.  
Additional Shelves & Shelf Weight Capacities, Page 62

#### SLIDING SHELVES FOR 19" MOUNTING

7206-FRSL-ADHD Front & rear mount sliding, (adj.) – 26.00"D, Wt. cap.: 110lbs.  
7206-FRSL-AHD Front & rear mount sliding, (adj.) – 22.00"D, Wt. cap.: 110lbs.  
7206-FRSLA300 Front & rear mount sliding, (adj.) – 30.00"D, Wt. cap.: 300lbs.  
Additional Shelves & Shelf Weight Capacities, Page 62

#### SPECIALTY SHELVES FOR 19" MOUNTING

7206-MKM Monitor/keyboard/mouse shelf  
7206-PKB-MT Pivoting keyboard tray with mouse tray.

#### POWER OUTLET STRIPS, COPPER BUS BARS & COOLING EQUIPMENT

7215 16 position power strip w/circuit breaker & 5-15P plug  
7215-20AR 16 position power strip w/circuit breaker & 5-20P plug  
7215-20ARTLP 20 AMP, 16 position power strip w/circuit breaker, & twist lock L5-20P plug  
7215-30A 24 position power strip, NEMA 5-20R receptacles, L5-30P plug  
CBB-78 Copper bus bar  
7217 Fan assembly w/fan guards & three 75 CFM fans- mounts to vented top (TPS2-2436)  
Additional Cooling Equipment, Page 63 Additional Power Outlet Strips, Pages 61, 69-72

#### CASTERS, LEVELERS, MOUNTING RAILS, & OTHER ACCESSORIES

7209-N Adjustable levelers (2.50" in height) – one set of four  
7208-E Casters – one set of four (2 locking and 2 non-locking)  
8405S21032 Pair of 19" mounting rails, tapped 10/32 w/hardware  
8405S2M6 Pair of 19" mounting rails to accept M6 cage nuts w/hardware  
G101 Networking/Ganging kit  
HDW-105-50 Package of 50 M6 cage nuts w/screws  
1.75-FP19 Filler panel, 1.75"H for 19" rack mounting, 1 RMU  
3.50-FP19 Filler panel, 3.50"H for 19" rack mounting, 2 RMU  
5.25-FP19 Filler panel, 5.25"H for 19" rack mounting, 3 RMU