

SWITCHVIEW IP 1020 REMOTE ACCESS DEVICE SPECIFICATIONS

MECHANICAL

- Height – 1.06 in. (2.70 cm)
- Depth – 5.25 in. 13.34 cm)
- Width – 8.19 in. (20.80 cm)
- Weight – 1.5 lbs. (0.68 kg) without cables
- Style – Desktop

ENVIRONMENTAL/POWER/HARDWARE

- Operating Temperature: 32° to 104°F (0° to 40°C)
- Storage: -22° to 158°F (-30° to 70°C)
- Operating Voltage: 5vDC
- Power Consumption: 5W
- Input: 10W maximum (120v, 60 Hz)
- Computers: USB and PS/2
- Video Modes: VGA compatible, local port maximum: 1600x1200 @ 75Hz, remote port maximum: 1280x1024 @ 75Hz
- Peripherals: PS/2 keyboard, PS/2 mouse

ORDERING DETAILS

- SwitchView IP 1020 Remote Access Device

SVIP1020-001 Single-port remote access device with on-board Web interface

STANDARDS

- Approved Agency

UL, FCC Class B, cUL, ICES-003 Class B, CE, GS, VCCI Class B, MIC Class A, C-Tick

WARRANTY

- Two years

The SwitchView IP 1020 remote access device includes an on-board Web interface for convenient and secure remote access to any existing KVM switch from any location. This solution includes a local KVM port for at-the-rack connectivity and an Ethernet port for remote connections.

