



Material:

- Carbon steel
- Enclosure: 16 ga (1.5 mm)
- Door: 14 ga (2.0 mm)
- Mounting panel: 11 ga (3.0 mm)

Surface finish:

- Enclosure and door: Dipcoat primed, powder painted on the outside in

- textured RAL 7035 (light grey)
- Mounting panel: Zinc-plated

Protection rating:


- UL Type 12 (IP 55 to EN 60 529/10.91), with selection of the appropriate gland plates, see page 707.
- CSA, cUL
- UL file #: E76083

Configuration:

- Enclosure with one door, right hand door hinge, may be changed to the opposite side,
- Mounting panel
- Open base for individual cable entry.

Detailed drawings:

Available



Depth: 12 - 16" (300 - 400 mm), Height: 32 - 55" (800 - 1400 mm)

Height (T) inches (mm)	PU	39 (1000)	39 (1000)	47 (1200)	47 (1200)	47 (1200)	55 (1400)	32 (800)	Page
Width (B) inches (mm)		32 (800)	39 (1000)	24 (600)	32 (800)	39 (1000)	39 (1000)	24 (600)	
Depth (T) inches (mm)		12 (300)	12 (300)	12 (300)	12 (300)	12 (300)	12 (300)	16 (400)	
Panel Height (G) inches (mm)		38 (955)	38 (955)	46 (1155)	46 (1155)	46 (1155)	53 (1355)	30 (755)	
Panel Width (F) inches (mm)		29 (740)	37 (940)	21 (540)	29 (740)	37 (940)	37 (940)	21 (540)	
Part No.	1	5114.500	5118.500	5112.500	5116.500	5119.500	5121.500	5110.500	
Door(s)		1	2	1	1	2	2	1	

Base/plinth

Components front and rear inches (mm)	Height 4 (100)	1 set	8601.800	8601.000	8601.600	8601.800	8601.000	8601.600	533
	Height 8 (200)	1 set	8602.800	8602.000	8602.600	8602.800	8602.000	8602.600	533
Side panels inches (mm)	Height 4 (100)	1 set	8601.030					8601.040	534
	Height 8 (200)	1 set	8602.030					8602.040	534

Accessories

Rail for interior installation	For height	4	5001.052	5001.052	5001.053	5001.053	5001.053	5001.054	5001.051	651
	For width	4	5001.051	5001.052	5001.050	5001.051	5001.052		5001.050	651
Matching system chassis with mounting flange	In width	4	8612.080	8612.000	8612.060	8612.080	8612.000		8612.060	652
	In depth	4	8612.130					8612.140	652	
Bottom cover plate		1	-					5001.130	557	

Note: CM gland plates (see page 707) or cover plate (see page 557) required for UL Type 12 rating.

CM compact enclosure

Depth: 16" (400 mm), Height: 39 - 55" (1000 - 1400 mm)

Height (T) inches (mm)	PU	39 (1000)	39 (1000)	47 (1200)	47 (1200)	47 (1200)	47 (1200)	55 (1400)	Page
Width (B) inches (mm)		24 (600)	32 (800)	24 (600)	32 (800)	39 (1000)	47 (1200)	39 (1000)	
Depth (T) inches (mm)		16 (400)	16 (400)	16 (400)	16 (400)	16 (400)	16 (400)	16 (400)	
Panel Height (G) inches (mm)		38 (955)	38 (955)	46 (1155)	46 (1155)	46 (1155)	46 (1155)	53 (1355)	
Panel Width (F) inches (mm)		21 (540)	29 (740)	21 (540)	29 (740)	37 (940)	45 (1140)	37 (940)	
Part No.	1	5111.500	5115.500	5113.500	5117.500	5120.500	5123.500	5122.500	
Door(s)		1	1	1	1	2	2	2	

Base/Plinth

Components front and rear inches (mm)	Height 4 (100)	1 set	8601.600	8601.800	8601.600	8601.800	8601.000	8601.200	8601.000	533
	Height 8 (200)	1 set	8602.600	8602.800	8602.600	8602.800	8602.000	8602.200	8602.000	533
Side panels inches (mm)	Height 4 (100)	1 set	8601.040							534
	Height 8 (200)	1 set	8602.040							534

Accessories

Rail for interior installation	For height	4	5001.052		5001.053				5001.054	651
	For width	4	5001.050	5001.051	5001.050	5001.051	5001.052	5001.053	5001.052	651
Matching system chassis with mounting flange	In width	4	8612.060	8612.080	8612.060	8612.080	8612.000	8612.020	8612.000	652
	In depth	4	8612.140							652
Bottom cover plate		1	5001.130	5001.140	5001.130	5001.140	5001.150	5001.160	5001.150	557

Note: CM gland plates (see page 707) or cover plate (see page 557) required for UL Type 12 rating.